

HIGHWAY 3

AGILE COMMERCIAL RIDE-ON CYLINDER MOWER



- **Fuel efficient cut with Ransomes® SPORT cylinders**
- **Safe on the road, with adaptable, precision cutting control**
- **Versatile, light & manoeuvrable**
- **Ease of access swing out centre cutting unit**

Specifically designed for the commercial market, the Ransomes Highway 3 triple cylinder mower brings class-leading functionality and finishing to parks, gardens, schools, sports grounds, community spaces and roadsides. Now with an updated, more efficient drivetrain, this Stage V emission compliant machine is highly productive yet manoeuvrable in tight spaces.

Operators can control each cutting unit individually or raise all three for easy transportation from site to site. With cutting unit options to suit all types of terrain, the Ransomes Highway 3 will raise your standards.

CUTTING WIDTH

2.13M
[84"]

HEIGHT OF CUT

12.7-89MM

[0.50-3.50"] Fixed heads
12.7-35.7 mm [0.5 - 1.4"] Floating

ENGINE TYPE

18.6kw

[24.8HP] Kubota® 3 cylinder diesel

CUTTING UNITS

3 FIXED/FLOATING

heads, 76cm [30"] x 20cm [8"] diameter
reels, 4, 6 & 8 blade options

**ANY LESS
COSTS MORE.**

For information and support:

www.ransomes.com / +44 [0] 1473 270 000



HIGHWAY 3 AGILE COMMERCIAL RIDE-ON CYLINDER MOWER

KEY ATTRIBUTES	
CUTTING WIDTH	2.13m [84"]
HEIGHT OF CUT	SPORT 200 Fixed: 12.7-89 mm [0.5 - 3.5"], SPORT 200 Floating: 12.7-35.7 mm [0.5 - 1.4"], Optional Thin Blade 9-32 mm [0.35 - 1.25"], Optional High Height Kit 12.7 - 61 mm [0.5 - 2.4"]
CUTTING CAPACITY	2.3 ha/hr at 12 km/h [5.68 acre/hr at 7.5 mph]
CUTTING UNITS	3 x 76 cm [30"] Ransomes SPORT 200 fixed or floating head cutting units
FUEL CAPACITY	43 L [9.45 gal.]
ENGINE	Kubota D1105 3 cylinder 18.6 kW [24.8 hp]
COOLING SYSTEM	Side by side hydraulic and engine cooler [11 fins per inch] with intermediate removable debris screen
ELECTRICAL SYSTEM	12 V
SAFETY & ROAD OPTIONS	Halogen / LED road lighting kit, amber warning beacon, Tilt Sensor Technology [TST], air suspension seat, storage racks, toolbox, armoured tyres and high height of cut kit.
CERTIFICATION	BSI approved: ISO 9001, ISO 14001, ISO 45001. Manufactured In UK
WARRANTY	2 years

TRACTION, BRAKES & SPEED	
TRACTION SYSTEM	On-demand cross-flow 4 wheel drive system, 2 wheel drive in transport mode. Direct coupled variable displacement pump.
REEL DRIVE	Fixed displacement hydraulic
HYDRAULIC SYSTEM	33 L [8.7 gal.] capacity regulated with side by side cooler
WEIGHT TRANSFER	Standard. Operate on demand to boost traction
SERVICE BRAKES	Dynamic braking through Hydrostatic traction system
PARKING BRAKES	Zero-maintenance electro-hydraulic wet parking brakes
TYRES	Front 6 ply 23 x 12.5-10, Rear 4 ply 18 x 8.5-8. Turf pattern
STEERING	Hydraulic power steering with tilt adjustable steering wheel
MOWING SPEED	Forward: 12 km/h [7.4 mph] Reverse: 12 km/h [7.4 mph]
TRANSPORT SPEED	Forward: 25 km/h [15.5mph] Reverse: 5 km/h [3mph]
REVERSE	5 km/hr [3 mph]


WEIGHTS & DIMENSIONS	
WEIGHT	1200 kg [2646 lbs.]
LENGTH	2.55 m [100.4"]
HEIGHT INCLUDING ROPS	2.11 m [83.07"]
WHEEL BASE	1.35 m [53.1"]
TRANSPORT WIDTH	1.37 m [54"] with SPORT units at 25 mm [1"] Height of Cut
WORKING WIDTH [MAX]	2.41 m [94.7"] Units Down




Fuel efficient cut with Ransomes® SPORT cylinders



Safe on the road, with adaptable, precision cutting control



Versatile, light & manoeuvrable



Ease of access swing out centre cutting unit



*Engine power is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use. Specifications, while correct at time of publishing, may change without notice. Requires Ultra Low Sulphur Diesel. Cutting Capacity 10% allowance for overlap.