

TR320

HIGH TRACTION CONTOUR TRIM MOWER



- **Trusted mowing on elite sports turf**
- **Premium cut quality**
- **Best transport and storage width**
- **Versatile, safe & manoeuvrable**

Introducing the TR320, a high traction contour trim mower offering you the perfect balance of comfort, cut quality and power. The highly manoeuvrable TR320 has contour following articulated reels with a trustworthy Kubota® engine, built to deliver the highest performance on the sports field or golf course, no matter the weather.

Designed to be transported and stored easily, with a narrow width, combined with zero-maintenance brakes, it has truly been designed with the user in mind. Regardless if your football, soccer, baseball, or fine sports turf is wet or dry and on flat or sloped terrain, you will always get our Signature Cut. Trusted by Generations.

CUTTING WIDTH

1.83M
[72"]

HEIGHT OF CUT

9.5-69.8MM
[0.5 - 1.85"]

CUTTING CAPACITY

1.83HA/HR
at 10 km/h [4.5 acre/hr x 6 mph]

MOWER ENGINE

18.6kw
[24.8hp] Kubota® D1105 3
cylinder 18.6 kW [24.8 hp]

ANY LESS COSTS MORE.

For information and support:
www.ransomes.com / +44 [0] 1473 270 000



TR320 HIGH TRACTION CONTOUR TRIM MOWER

KEY ATTRIBUTES	
CUTTING WIDTH	1.83 m [72"]
HEIGHT OF CUT	12 - 47 mm [0.5 - 1.85"]
CUTTING CAPACITY	1.83 ha/hr x 10 km/h [4.5 acre/hr x 6 mph]
FUEL CAPACITY	28.7L [7.6 gal.]
ENGINE	Kubota® D1105 3 cylinder 18.6 kW [24.8 hp]
EMISSIONS	EU Stage V - (EPA Tier 4 Final) compliant
OPERATOR STATION	Easy access operator position with superb all around visibility. Ergonomic armrest for all operator controls.
SAFETY & ROAD OPTIONS	Slick tyres, verticutting reels, grass baskets, light kit, backlap kit, canopy, weight transfer kit
CERTIFICATION	BSI approved: ISO 9001, ISO 14001, ISO 45001. Manufactured In UK
WARRANTY	2 years
CUTTING UNITS	
NUMBER & SIZE	66 cm [26"] wide x 16.5 cm [6.5"] Diameter. 5, 7 or 11 blade options.
BLADES PER REEL	5, 7 or 11
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT CONTROLS	Switch operated
TRACTION, BRAKES & SPEED	
TRACTION DRIVE	Parallel-series "on demand" 3WD
REEL DRIVE	Fixed displacement hydraulic
HYDRAULIC SYSTEM	40 L [10 gal.] capacity regulated with side by side cooler
SERVICE BRAKES	Dynamic braking through hydrostatic drive
PARKING BRAKES	Zero-maintenance electro-hydraulic wet parking brakes
STEERING	Hydraulic power steering with adjustable tilt steering wheel
MOWING SPEED	10km/h [6.2mph]
TRANSPORT SPEED	14km/h [8.7mph]
WEIGHTS & DIMENSIONS	
WEIGHT	747 kg [1646.9 lbs.]
LENGTH	2.46m [97"]
HEIGHT (INCLUDING ROPS)	2.04m [80"]
WHEEL BASE	1.36m [43.5"]
TRANSPORT WIDTH	1.66m [65.5"]
WORKING WIDTH	2.11 m [83"] Units Down



Trusted mowing on elite sports turf



Premium cut quality



Best transport and storage width



Versatile, safe & manoeuvrable



Specifications, while correct at time of publishing, may change without notice. Requires Ultra Low Sulphur Diesel. Cutting Capacity 10% allowance for overlap.